



<b>Model</b>	GX 16 - 21 SA
<b>Carrying Capacity</b>	16,000kg. Unladen weight 3,660kg
<b>Maximum Trailer Speed</b>	20mph
<b>Body</b>	Dimensions: 6100x2450x1500mm Hydraulically operated rear door Access ladder outside body Rope hooks on every body panel
<b>Floor Bearers</b>	75x50 aluminium square tube
<b>Body Frame</b>	75x50 aluminium square tube
<b>Top Rail</b>	100x60 aluminium square tube
<b>Floor</b>	5mm aluminium
<b>Sides</b>	4mm aluminium
<b>Chassis</b>	250x150 steel box section
<b>Top Chassis</b>	180x75 aluminium channel
<b>Axles</b>	Granning 125mm ø 10 stud, 420x180 brakes
<b>Suspension</b>	Granning overslung 4 spring suspension
<b>Drawbar</b>	4 leaf springs Sprung drawbar Heavy duty 40mm hitch eye
<b>Wheel Centres</b>	Rear heavy duty 40mm tow eye welded to rear chassis
<b>Tyres</b>	10 stud fully welded high speed rims Remould 385/65Rx22.5
<b>Braking</b>	Mud wings and spray suppression flaps Hydraulic braking system
<b>Lighting</b>	Ratchet style parking brake LED Commercial road lighting system Connection to tractor: Removable electric coil Rear stop/tail/indicator lights Front marker lights Side marker lights High level rear marker lights Amber warning light
<b>Tipping Mechanism</b>	Twin 3 stage 4.25" diameter chrome plated tipping rams, 35mm ram pins with grease points 60mm hinge bar with bushes and grease points
<b>Paint</b>	Finished with 120 microns of two pack acrylic high gloss paint
<b>Optional Extras</b>	Fast tow trailer with air braking, ABS & LSV, Silage Sides, Roll over cover, Grain hatch, Flotation tyres, Front window/ view grille, High level road lights
<b>Alternative model</b>	GX16 - 21 LA. Body dimensions 6700x2450x1370mm